

MOTOR RUN CAPACITORS



LCR TYPE	MR/P	MR/P	MR/PF
RATED DC VOLTAGE AC	250 VAC	440 VAC	440 VAC
CAPACITANCE RANGE	1 - 180 μ F	1 - 95 μ F	1 - 4 μ F
CAPACITANCE TOLERANCE \pm %	5%, 10%, 20%	5%, 10%, 20%	5%, 10%, 20%
TERMINATION	MAINS CABLE/ FLYING LEADS/TAG	MAINS CABLE/ FLYING LEADS/TAG	MAINS CABLE/ FLYING LEADS/TAG
CLIMATIC CATEGORY	25-085-21	25-085-21	25-085-21
PULSE RISE TIME dV/dT	50V/ μ s	50V/ μ s	50V/ μ s
HOUSING	PLASTIC	PLASTIC	PLASTIC

MOTOR RUN CAPACITORS



LCR TYPE	MR/A	MR/A	MR/A
RATED DC VOLTAGE AC	250 VAC	440 VAC	440 VAC
CAPACITANCE RANGE	1 - 180 μ F	1 - 95 μ F	1 - 95 μ F
CAPACITANCE TOLERANCE \pm %	5%, 10%, 20%	5%, 10%, 20%	5%, 10%, 20%
TERMINATION	FLYING LEADS/ MAINS CABLE/TAG	FLYING LEADS/ MAINS CABLE/TAG	FLYING LEADS/ MAINS CABLE/TAG
CLIMATIC CATEGORY	25-085-21	25-085-21	25-085-21
PULSE RISE TIME dV/dT	50V/ μ s	50V/ μ s	50V/ μ s
HOUSING	ALUMINIUM	ALUMINIUM	ALUMINIUM