

## POWER APPLICATION CAPACITORS



LCR TYPE	C/A/R/S	PES/HM/F	PE/A	PE/A
RATED DC VOLTAGE AC	660 VAC	630 - 900 VAC	250 VAC	440 VAC
CAPACITANCE RANGE	1 - 30 $\mu$ F	0.1 - 11 $\mu$ F	1 - 180 $\mu$ F	1 - 95 $\mu$ F
CAPACITANCE TOLERANCE $\pm$ %	5%, 10%, 20%	5%, 10%, 20%	5%, 10%, 20%	5%, 10%, 20%
TERMINATION SPACING	SCREW	MAINS CABLE/ FLYING LEADS/TAG	MAINS CABLE/ FLYING LEADS/TAG	MAINS CABLE/ FLYING LEADS/TAG
CLIMATIC CATEGORY	25-085-21	25-070-21	25-085-21	40-085-21
PULSE RISE TIME $dV/dt$	>250V/ $\mu$ s	>250V/ $\mu$ s	>50V/ $\mu$ s	50V/ $\mu$ s
HOUSING	ALUMINIUM/PLASTIC	ALUMINIUM/PLASTIC	ALUMINIUM/PLASTIC	ALUMINIUM/PLASTIC

## POWER FACTOR CORRECTION UNITS



LCR TYPE	PFM	PFM/ULL	PF3/ULL	PFC SERIES
RATED DC VOLTAGE AC	440 VAC	440 VAC	440 VAC	415 VAC
CAPACITANCE RANGE	0.6 - 3.9 KVAR	0.6 - 2.4 KVAR	2.7 - 5.8 KVAR	0.5 - 10 KVAR
CAPACITANCE TOLERANCE $\pm$ %	5%, 10%	5%, 10%	5%, 10%	5%, 10%
TERMINATION SPACING	FLYING LEADS	FLYING LEADS	3 WAY TERM BLOCK	MAINS CABLE
CLIMATIC CATEGORY	-20/+50°C	-20/+50°C	-20/+50°C	-25/+85°C
FREQUENCY	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz
HOUSING	PLASTIC	PLASTIC	ALUMINIUM	ALUMINIUM